



Bearing No. PF 40 WF

Size	40x3.5x10 mm
Bore Diameter	40 mm
Outer Diameter	3,5 mm
Width	10 mm
d	40 mm
A ₁	3.5 mm
A ₂	10 mm
B	42.8 mm
B ₄	6.75 mm
D _a - min.	87 mm
J	119 mm
H	148 mm
H	13.5 mm
s ₁	34.9 mm
T	38.4 mm
Basic dynamic load rating - C	30.7 kN
Basic static load rating - C ₀	19 kN
Fatigue load limit - P _u	0.8 kN
Permissible radial housing load	max. 7.5 kN
Weight	1.35 kg
Thread - G ₂	M10x1
Hexagonal key size for grub screw - H	5 mm
Housing material	Pressed steel
A ₁	3.5 mm
A ₂	10 mm
B ₄	6.75 mm

D _a min.	87 mm
N	13.5 mm
s ₁	34.9 mm
Basic dynamic load rating C	30.7 kN
Basic static load rating C ₀	19 kN
Fatigue load limit P _u	0.8 kN
Permissible radial housing load max.	7.5 kN
Mass unit	1.35 kg
Thread grub screw G ₂	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in
Bearing	YEL 208-2F
Housing	PF 80